


# DIN 6799

## Retaining washers

for shafts



d2	for Ø	d3	s	a
1,2	1,4 - 2,0	3,25	0,30	1,01
1,5	2,0 - 2,5	4,25	0,40	1,28
1,9	2,5 - 3,0	4,80	0,50	1,61
2,3	3,0 - 4,0	6,30	0,60	1,94
3,2	4,0 - 5,0	7,30	0,60	2,70
4,0	5,0 - 7,0	9,30	0,70	3,34
5,0	6,0 - 8,0	11,30	0,70	4,11
6,0	7,0 - 9,0	12,30	0,70	5,26
7,0	8,0 - 11,0	14,30	0,90	5,84
8,0	9,0 - 12,0	16,30	1,00	6,52
9,0	10,0 - 14,0	18,80	1,10	7,63
10,0	11,0 - 15,0	20,40	1,20	8,32
12,0	13,0 - 18,0	23,40	1,30	10,45
15,0	16,0 - 24,0	29,40	1,50	12,61
19,0	20,0 - 31,0	37,60	1,75	15,92
24,0	25,0 - 38,0	44,60	2,00	21,88

Grade	SU
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	100
1.4122	100
1.4122	50
1.4122	50
1.4122	50

■ A1 / ▲ A2 / ● A4 | SU: Sales unit | All measurements in mm | Other dimensions on request.  
 Example item no. 6799-2-8 DIN 6799 - 1.4122 - Ø 8mm - \*1 unclamped - \*2 clamped